



## 4-PORT SUPERSPEED USB 3.0 HUB

### **SUPER SPEED USB 3.0**

Transfer files up to 10 times faster than through USB 2.0

### **COMPATIBLE WITH YOUR DEVICES**

Backwards compatibility with USB 2.0 and 1.1 ensures that you can connect all your USB devices

### **SLEEK, COMPACT DESIGN**

Its glossy exterior looks great on your desktop, or just slip it into your laptop bag



### **BLAZING USB 3.0 SPEED**

Connect to USB 3.0 devices at blazing speeds of up to 5 Gbps - up to 10 times faster than USB 2.0. You can back up your photos, music, and HD movies to an external storage device faster than ever before.

### **CONNECT ALL YOUR PERIPHERALS**

Backward compatibility with USB 2.0 and USB 1.1 means that you can connect any USB device to the DUB-1340. If you need more ports, you can connect additional USB hubs to connect up to 127 devices.

### WHAT THIS PRODUCT DOES

The 4-Port SuperSpeed USB 3.0 Hub provides an additional four USB 3.0 ports, allowing you to connect peripherals such as external storage, digital cameras, printers, and more.



**USB 2.0/3.0 CONNECTOR**  
Connects to a USB 2.0 or 3.0 host port

**POWER CONNECTOR**  
Connects to the power adapter

## TECHNICAL SPECIFICATIONS

### INTERFACE

- 4 downstream USB Type A (female) ports
- 1 upstream USB Type Micro-B (female) port

### STANDARDS

- USB specification version 3.0
- USB specification version 2.0
- USB specification version 1.1<sup>1</sup>
- USB specification version 1.0
- OHCI (Open Host Controller Interface)
- EHCI (Enhanced Host Controller Interface)

### DATA RATES

- SuperSpeed: 4.8 Gbps
- Hi-Speed: 480 Mbps
- Full Speed: 12 Mbps
- Low Speed: 1.5 Mbps

### CONNECTIVITY

- Up to 127 devices by cascading multiple hubs

### SYSTEM REQUIREMENTS

- Available USB port

### SUPPLIED POWER

- Maximum 900 mA per port (with external AC adapter)

### POWER

- External power adapter 5 V / 4 A

### DIMENSIONS (L x W x H)

- 72.45 x 97.97 x 20.27 mm (2.9 x 3.9 x 0.8 inches)

### WEIGHT

- 60 grams

### OPERATING TEMPERATURE

- 0 to 40 °C (32 to 104 °F)

### STORAGE TEMPERATURE

- -20 to 50 °C (-4 to 122 °F)

### OPERATING HUMIDITY

- 0% to 80% (non-condensing)

### PACKAGE CONTENTS

- D-Link 4-Port SuperSpeed USB 3.0 Hub
- Power adapter
- USB 3.0 cable

### CERTIFICATIONS

- FCC
- CE

<sup>1</sup> Both the host and client device must support the same data rate in order to transfer data at that rate.



**D-Link Corporation**  
No. 289 Xinhu 3rd Road, Neihu, Taipei 114, Taiwan  
Specifications are subject to change without notice.  
D-Link is a registered trademark of D-Link Corporation and its overseas subsidiaries.  
All other trademarks belong to their respective owners.  
©2010 D-Link Corporation. All rights reserved.  
Release 01 (November 2010)